

# METHOD AND APPARATUS FOR STABILIZING CONTAMINATED SOIL/WASTE

Publication number: JP2004167374

Publication date: 2004-06-17

Inventor: SHIBATA TAISUKE; KONDO ATSUSHI; TAKIGAWA NOBORU

Applicant: KAWASAKI HEAVY IND LTD

Classification:

- international: A62D3/00; B09B3/00; B09C1/02; B09C1/08; C02F11/00; A62D3/00; B09B3/00; B09C1/00; C02F11/00; (IPC1-7): B09B3/00; B09C1/02; B09C1/08; C02F11/00

- european:

Application number: JP20020336057 20021120

Priority number(s): JP20020336057 20021120


Report a data error here

## Abstract of JP2004167374

**PROBLEM TO BE SOLVED:** To surely stabilize various kinds of contaminated soil or/and single or combined waste in a short period of time independently of a season and a location.

**SOLUTION:** In a stabilization method, a lime material and/or a silica material are added to contaminated soil or/and at least either waste among combustion ash and sludge resulted from paper-making sludge, wood chip, organic sludge, trash and coal and amount of CaO is adjusted to 2.5 to 35 weight % and the amount of SiO<sub>2</sub> is adjusted to 25 to 65 weight %. Kneading with water in which a reducing material of 0.25 to 15 weight % to the contaminated soil or/and the waste is dissolved, is executed in a kneading machine 10 to give the mixture a funicular state. Then steam treatment at 40 to 100[deg.]C for 0.5 to 24 hours in a steam treatment machine 12 gives a stable treated material.

COPYRIGHT: (C)2004,JPO



Data supplied from the esp@cenet database - Worldwide